

# KingMix<sup>®</sup> 753PC

New generation hyperplasticising admixture for extended slump retention.

## DESCRIPTION

KingMix 753PC is a new generation hyperplasticiser for concrete, specially designed to produce concrete with extensive workability.

This effect can be used to produce low viscosity concrete for mid-to-high scale projects or when pumping concrete over long distances is required.

## APPLICATIONS

- ☐ For high levels of concrete pumping.
- ☐ Suitable for long distances with extended slump retention.
- ☐ Low viscosity concrete with Enhanced compressive strength.
- ☐ Structures with congested reinforcement.
- ☐ Pre-stressed concrete.
- ☐ Improved cohesion allows for use in mass concrete pours and piling.

## COMPATIBILITY

KingMix 753PC suitable to use with all types of Portland cement and cement replacement materials. KingMix 753PC is compatible with other KINGKRETE admixtures used in the same concrete mix.

If more than one type of admixture will be used in the concrete mix, they must be dispensed to the concrete separately.

## STANDARDS

KingMix 753PC complies with ASTM C494, Type F and G, depending on dosage used.

## METHOD OF USE

KingMix 753PC should be added to the concrete with the mixing water to achieve optimum performance.

An automatic dispenser should be used to dispense the correct quantity of KingMix 753PC to the concrete mix.

## TECHNICAL PROPERTIES @ 25°C:

Colour:	Light yellow liquid
Specific gravity:	1.07 ± 0.02
pH:	5 - 7

## DOSAGE

The recommended dosage of KingMix 753PC is 1.0 - 3.5 litre per 100 kg of cementitious materials in the mix, including GGBFS, PFA or micro-silica.

Representative trials should be conducted to determine the optimum dosage of KingMix 753PC to meet the performance requirements by using the materials and conditions in actual use.

## EFFECTS OF OVER DOSAGE

Over dosing of KingMix 753PC will cause the following:

- ☐ Increase in workability.
- Ultimate concrete strength will not be adversely affected and will generally be increased provided that proper concrete curing is maintained.

## CLEANING

KingMix 753PC can be washed with fresh cold water.

## PACKAGING

KingMix 753PC is available in 25 litre jerrycan, 210 litre drums and 1000 litre bulk supply.

## STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.



# KingMix<sup>®</sup> 753PC

## HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

## NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative. KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

## QUALITY AND CARE

All products originating from KingKrete's Qatar facility are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

\* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

## KingKrete-Qatar/KingMix\_753PC\_02/v2/07\_18

### STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

K

### NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

