

KingPro[®] GP

Ready to use gypsum board joint putty

DESCRIPTION

Pre-mixed compound used for joint filling and as finishing coat for interior gypsum panels.

APPLICATIONS

- KingPro GP is designed for use internally, to fill joints between adjacent gypsum boards in conjunction with an appropriate mesh.
- Used for covering corner bead, fasteners and other small openings, trim and as a skim coating for the entire gypsum panel surface.

ADVANTAGES

- Pre-mixed, ready for use.
- Superior ease of application.
- Flexible, resists cracking.
- Excellent adhesion.
- Adhesion unaffected under humid conditions.

METHOD OF USE

Preparation

Stir contents lightly without adding water, avoid over mixing as it may cause air entrapment. Do not mix with any other material. Joints and all surfaces should be dry and clean.

Application

- Fill space between panels with KingPro GP and tightly embed with a trowel.
- Place mesh over the joint and smoothen out to remove any bulges.
- Apply KingPro GP over mesh and smoothen out the surface.
- Apply further coats as may be required and allow to dry.
- Remove any edges by sanding with a fine grade sand paper after drying.

CLEANING

Wash tools with warm, soapy water, wipes tools dry to prevent rusting.

TECHNICAL PROPERTIES @ 25°C:

Appearance:	Smooth, creamy, lump free paste
Colour:	White
Specific gravity:	1.75 - 1.85 kg/m ³
Curing time:	> 2 hrs.

PACKAGING

KingPro GP is available in 5 and 25 kg buckets.

COVERAGE

Approximately 1.8 kg/ m² @ 1 mm thickness.

STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.



KingPro[®] GP

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative. KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from KingKrete's Qatar facility are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

KingKrete-Qatar/Kingpro_GP_02/v2/07_18

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

KingKrete Trading & Contracting W.L.L
Doha – State of Qatar
www.kingkreteinc.com

Disclaimer: the IAS mark relates to certified management system and not to the product mentioned on this datasheet

