

# KingCoat<sup>®</sup> Primer P

Epoxy based primer.

## DESCRIPTION

KingCoat Primer P is a multi-component solvent based epoxy primer especially formulated to be used in conjunction with KingCoat A100 to significantly improve its adhesion characteristics on steel and concrete surfaces.

KingCoat Primer P is supplied in form of epoxy base material and hardener which should be mixed together prior to using, it can be also supplied with a colour pack to match the colour of the topcoat material and thus lower the consumption of KingCoat A100 and provide a uniform finishing.

## ADVANTAGES

- Ⓛ Significantly improves the adhesion of KingCoat A100 over concrete and steel substrates.
- Ⓛ Easy to apply, can be spread by roller, brush or airless spray.
- Ⓛ Can be supplied in different colours to match the colour of the topcoat material.

## METHOD OF USE

### Substrate Preparation

Concrete substrates should be sound, clean and free from contaminations. Surface laitance should be removed by grit blasting or water jetting. All exposed pinholes should be filled with epoxy paste using KingRep EP10.

Steel substrates should be grit blasted to reach a bright finish meeting the requirement of Swedish Standard SA 2 1/2.

### Mixing

Prior to mixing, stir individual components to disperse any settlement.

Add the entire content of the colour pack (if available) into the base container and mix with heavy duty drill for 2 minutes till a uniform colour is achieved. Add the entire content of the hardener to the base and mix thoroughly for 2 - 3 minutes.

## TECHNICAL PROPERTIES @ 25°C:

Mixed density:	1.35 ± 0.05 g/cm <sup>3</sup>
Pot life:	2.5 - 3.5 hr
Over-coating time:	
Minimum	6 hr
Maximum	24 hr
Full cure:	7 days
Bond strength on C25/30 concrete: ASTM D4541	≥ 2.0 MPa @ 7 days (concrete failure)

## Application

Use brush, lamb's wool roller, or airless spray machine to apply. KingCoat Primer P should be applied on the prepared substrates at a rate of 5.5 - 6.5 m<sup>2</sup>/kg to achieve 70 - 80 microns dry film thickness.

KingCoat Primer P should be left to completely reach a tack-free condition before being overcoated with KingCoat A100, typically, this can be achieved within 6 to 24 hours at normal ambient conditions.

## CLEANING

All tools should be cleaned immediately after application using DCP Solvent. Hardened materials must be cleaned mechanically.

## PACKAGING

KingCoat Primer P is available in 5 kg packs (3.85 litre) and 20 kg packs (15.4 litre).

## COVERAGE

Approximately 5.5 - 6.5 m<sup>2</sup>/kg to achieve 70 - 80 microns dry film thickness.

## STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.



# KingCoat<sup>®</sup> Primer P

## HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

## NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative. KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

## QUALITY AND CARE

All products originating from KingKrete's Qatar facility are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

\* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

## KingKrete-Qatar/KingCoat\_Primer P\_02/v2/07\_18

### STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

K

### NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

KingKrete Trading & Contracting W.L.L  
Doha – State of Qatar  
www.kingkreteinc.com

**Disclaimer:** the IAS mark relates to certified management system and not to the product mentioned on this datasheet

