



KingForm[®] 100SR

Water based gel surface retarder for concrete.

DESCRIPTION

KingForm 100SR is a ready for use, water based. Single component, concrete gel surface retarder.

APPLICATIONS

KingForm 100SR is used to produce an exposed aggregate concrete finish and to produce mechanically good construction joint. KingForm 100SR is ideally designed for use in either face up or face down concrete elements in the following applications:

- ☐ All types of cast in situ concrete elements.
- ☐ Pre-cast concrete elements.
- ☐ Construction and Contraction joints.

ADVANTAGES

- ☐ Single component, easy to apply.
- ☐ Suitable for all types of concrete elements, shapes and strengths.
- ☐ No independent release agent required.
- ☐ Can be used for both face up and face down applications.

METHOD OF USE

Surface Preparation

Formwork must be non-porous and cleaned of surface deposits, rust, concrete, oil or other materials. Porous timber and formwork should be coated with suitable polyurethane sealer.

Application

- ☐ KingForm 100SR should be mixed well before use by suitable mechanical mixer.
- ☐ KingForm 100SR can be applied using brush, spray or roller at a rate of 0.1 – 0.2 liters/ m²/ coat. One coat is normally needed.
- ☐ To obtain face down finish, KingForm 100SR shall be applied and left for 20 – 25 minutes to reach a complete dryness before placing concrete. However, touch dry time varies depending upon ambient temperature.
- ☐ To obtain face up applications, immediately after final finishing of concrete surfaces and whilst the concrete is still wet, KingForm 100SR should be spray applied at the rate of 0.15 – 0.25 liters/ m².
- ☐ Once the concrete shutter or moulds removed or the face up concrete surfaces reached final setting, the retarded portion of concrete surface layer is easily removed by water washing or wire brush.

NOTE

Application of KingForm 100SR for the face up applications should not begin until the concrete is free from surface water, and should not commence at all if bleed water is apparent on the concrete surface.

PACKAGING

KingForm 100SR is available in 18 liters drums.

STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative.

KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.



KingForm[®] 100SR

QUALITY AND CARE

All products originating from KingKrete's Qatar facility are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

KingKrete-Qatar/KingForm_100SR_02/v2/07_18

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

n

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

KingKrete Trading & Contracting W.L.L
Doha – State of Qatar
www.kingkreteinc.com

Disclaimer: the IAS mark relates to certified management system and not to the product mentioned on this datasheet

