

KingProof[®] B200

Water based rubberized bitumen protective coating.

DESCRIPTION

KingProof B200 is a dark brown emulsified bitumen liquid reinforced with rubber and formulated from selected raw materials to form a flexible water proofing and protective coating for concrete and masonry.

APPLICATIONS

KingProof B200 provides a water proofing and protective coating for:

- ☐ Retaining walls.
- ☐ Shaded or tiled roofs.
- ☐ Underground concrete basements, walls and foundations.
- ☐ Wet floor areas such as bathrooms and kitchens.

ADVANTAGES

- ☐ Resists attack by chloride and sulphate ions present in ground water.
- ☐ Single component.
- ☐ Applied by brush which make it easy to use.
- ☐ Economical.
- ☐ Solvent free, non flammable.
- ☐ Asbestos free.
- ☐ Does not rot.

STANDARDS

KingProof B200 complies with ASTM D1227-95, Type III, Class 1.

KingProof B200 complies with ASTM C309-93 when applied with two coats at a rate of 2 m²/litre.

METHOD OF USE

Surface Preparation

Surface preparation is very important to get the highest performance of KingProof B200. Any surface to be coated must be clean, sound and free of oil or grease. Any oil or grease contamination should be removed with a chemical degreaser. All holes should be filled with a suitable cementitious mortar before application of KingProof B200.

Primer Coat

There is generally no need for primer coat. Dusty surfaces should be primed with a coat of KingProof B200, diluted with an equal quantity of cool, clean water and allowed to dry.

TECHNICAL PROPERTIES @ 25° C

Form	Liquid
Density	1 ± 0.02 g/cm ³
Over coating time	10 hr
Solid content	Minimum 60%
Rubber content in dry film	Minimum 10%
Application temperature	5 - 45° C
Drying time:	3 - 5 hr
VOC	< 40 gr/ ltr

APPLICATION

It is recommended that two coats of KingProof B200 be applied. The second coat should be applied at a right angle to the first coat. Allow a minimum of 3 hours between coats. Stir well before use. KingProof B200 may be applied by brush, broom or squeegee.

COVERAGE

Coverage rate depends on surface roughness and the method of application.

- ☐ 3 - 5 m²/litre/coat, as protective coating.
- ☐ 1 - 1.5 m²/litre/coat, as waterproof coating giving a dry film thickness of 600 microns per coat. Two coats are recommended.

CLEANING

Tools and equipment can be cleaned with water when still wet. Dried KingProof B200 may be removed with KINGKRETE Solvent.

PACKAGING

KingProof B200 is available in 18 and 200 litre drums.

STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.



KingProof[®] B200

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative.

KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from KingKrete's Qatar facility are manufactured under a management system independently certified to conform to the requirements of the quality standard ISO 9001.

* Properties listed are based on laboratory-controlled tests.

® = Registered trademark of the KingKrete-Group in many countries.

KingKrete-Qatar/KingProof_B200_02/v2/07_20

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.